ELECTRONIC MICROMETERS

795.1 ELECTRONIC **M**ICROMETERS (WITH OUTPUT)

0-4"/0-100MM

796.1 ELECTRONIC **M**ICROMETERS (WITHOUT OUTPUT)

0-4"/0-100MM

The expanded 795.1 and 796.1 Micrometer offering now includes measuring ranges up to 4" (100mm). All are IP67 protected against coolant, water, chips, dirt and dust. The 795.1 is equipped with an RS232 output port and is ideal for use with DataSure® Wireless Data Collection Systems or Multiplexer Inupt. Sets available upon request.

FEATURES AND SPECIFICATIONS

- Large, easy-to-read .275" (7mm), high-contrast LCD digital readout
- Starrett no-glare satin chrome finish on thimble and sleeve
- Balanced and tapered frame
- Extremely hard and stable one-piece spindle
- Micro-lapped carbide measuring faces
- · Auto OFF after 20 minutes of nonuse
- Inch/millimeter conversion on English versions
- Measurement HOLD button
- Zero at any position
- Retain and return to true zero reading
- Resolution: .00005" (0.001mm)
- Accuracy: ±.0001" (±.002mm)

795.1 Electronic N	Micrometers with Outp	ut					
	Spindle Lock, Shell		Nut, Shell and Thimble	Ratchet Thimble,	Spindle Lock, Shell and	i	
Thimble Inch Grads.		Inch Grads.	Inch Grads.		Thimble Metric Grads.*		
Cat. No.	EDP	Cat. No.	EDP	Cat. No.	EDP		
795.1XFL-1	01100	795.1XRL-1	01108	795.1MXRL-25	01112	0-1" and 0-25mm	
795.1XFL-2	01101	795.1XRL-2	01109	795.1MXRL-50	01113	1-2" and 25-50mm	
795.1XFL-3	01102	795.1XRL-3	01110	795.1MXRL-75	01114	2-3" and 50-75mm	
795.1XFL-4	01103	795.1XRL-4	01111	795.1MXRL-100	01115	3-4" and 75-100mm	
796.1 Electronic N	Aicrometers without O	utput					
796.1XFL-1	01104	796.1XRL-1	01116	796.1MXRL-25	01120	0-1" and 0-25mm	
796.1XFL-2	01105	796.1XRL-2	01117	796.1MXRL-50	01121	1-2" and 25-50mm	
796.1XFL-3	01106	796.1XRL-3	01118	796.1MXRL-75	01122	2-3" and 50-75mm	
796.1XFL-4	01107	796.1XRL-4	01119	796.1MXRL-100	01123	3-4" and 75-100mm	
Sets							
Cat. No.	EDP	Range	Description				
S795.1AXFLZ	72534	0-3" (0-75mm)	Electronic micrometer set (set of 3), includes 795.1XFL-1, 795.1XFL-2, 795.1XFL-3				
S795.1BXFLZ	72535	0-4" (0-100mm)	Electronic micrometer set (set of 4), includes 795.1XFL-1, 795.1XFL-2, 795.1XFL-3, 795.1XFL-4				
Cables and Access							
Cat. No.	EDP	Description					
795.1SCM	01124		SmartCable to multiplexer				
795.1SCKB	01125	USB cable to PC (In fo	USB cable to PC (In focused window)				
795.1SCU	01126	SmartCable with USB	SmartCable with USB keyboard output				
PT99492	65650	Two 3-Volt Batteries,	Two 3-Volt Batteries, CR2032				
*Metric Only							

All 795.1 and 796.1 Micrometers include a protective case. All except 1" and 0-25mm sizes furnished with standards.





IP PROTECTION

An IP number is composed of two numbers, the first referring to protection against solid objects and the second against liquids.



First number 6: Totally protected against dust

Second number 7: Protection against submersion in water under standardized conditions of pressure for 30 minutes

All 795.1 and 796.1 Micrometers include IP67 protection



