


# D 32 (AF) LLAVE DE VASO 3/4"

perfil UD

- > Con cuadradillo de accionamiento interior según DIN 3120 - D 20, ISO 1174, con seguro de pasador
- > Uso manual, moleteado en cruz
- > Acero al vanadio GEDORE 31CrV3, cromado



Ø AF	L	d <sub>1</sub>	d <sub>2</sub>	t	⚖	Código	Nº
7/8	51,5	33,6	36,0	19,0	0,227	6274020	D 32 7/8AF
15/16	51,5	35,6	38,0	19,5	0,262	6274100	D 32 15/16AF
1	51,5	37,6	36,0	22,0	0,229	6274290	D 32 1AF
1.1/16	54,5	39,6	36,0	24,0	0,256	6274370	D 32 1.1/16AF
1.1/8	54,5	41,5	36,0	24,0	0,268	6274450	D 32 1.1/8AF
1.1/4	57,5	45,5	38,0	27,0	0,333	6274530	D 32 1.1/4AF
1.5/16	57,5	47,5	40,0	26,5	0,377	6274610	D 32 1.5/16AF
1.3/8	59,5	49,5	40,0	28,0	0,407	6274880	D 32 1.3/8AF

Ø AF	L	d <sub>1</sub>	d <sub>2</sub>	t	⚖	Código	Nº
1.7/16	59,5	51,4	40,0	28,0	0,413	6274960	D 32 1.7/16AF
1.1/2	59,5	53,3	40,5	28,0	0,431	6275180	D 32 1.1/2AF
1.5/8	62,5	57,4	44,0	30,5	0,539	6275260	D 32 1.5/8AF
1.11/16	62,5	59,4	44,0	30,5	0,568	6275340	D 32 1.11/16AF
1.3/4	65,5	61,4	44,0	32,5	0,627	6275420	D 32 1.3/4AF
1.13/16	65,5	63,3	44,0	32,5	0,637	6275500	D 32 1.13/16AF
1.7/8	65,5	65,3	44,0	32,5	0,664	6275690	D 32 1.7/8AF
2	68,5	69,2	48,0	34,5	0,811	6275770	D 32 2AF

# IN 32 VASO DESTORNILLADOR 3/4"

para tornillos hexagonales


- > Ejecución según DIN 7422
- > Con cuadradillo de accionamiento interior según DIN 3120 - D 20, ISO 1174, con seguro de pasador
- > Uso manual, moleteado en cruz
- > Cromado
- > Con espiga encajada a presión de acero al vanadio especial GEDORE, fosfatado al manganeso



IN 32 14



IN 32 22




Ø mm	L <sub>1</sub>	L <sub>2</sub>	d	⚖	Código	Nº
14	80	25,5	38	0,352	6275850	IN 32 14
17	80	25,5	38	0,394	6275930	IN 32 17

Ø mm	L <sub>1</sub>	L <sub>2</sub>	d	⚖	Código	Nº
19	80	25,5	38	0,433	6276070	IN 32 19
22	80	25,5	38	0,482	6276150	IN 32 22

# IN 32 L VASO DESTORNILLADOR 3/4"

para tornillos hexagonales, forma larga

- > Ejecución según DIN 7422
- > Con cuadradillo de accionamiento interior según DIN 3120 - D 20, ISO 1174, con seguro de pasador
- > Uso manual, moleteado en cruz
- > Cromado
- > Con espiga encajada a presión de acero al vanadio especial GEDORE, fosfatado al manganeso



Ø mm	L <sub>1</sub>	L <sub>2</sub>	d	⚖	Código	Nº
14	155	100	38	0,452	2003503	IN 32 L 14-155
17	155	100	38	0,540	1353705	IN 32 L 17-155
19	155	100	38	0,610	2003511	IN 32 L 19-155
22	155	100	38	0,730	2003538	IN 32 L 22-155

# ITX 32 VASO DESTORNILLADOR 3/4"

para tornillos TORX® hembra


- > Con cuadradillo de accionamiento interior según DIN 3120 - D 20, ISO 1174, con seguro de pasador
- > Uso manual, moleteado en cruz
- > Cromado
- > Con espiga encajada a presión de acero al vanadio especial GEDORE, fosfatado al manganeso
- > TORX® = marca registrada de la empresa Acument Intellectual Properties, LLC. EE.UU.



ITX 32 T60



ITX 32 T80



Ø	□ mm	✦ mm	L <sub>1</sub>	L <sub>2</sub>	d	⚖	Código	Nº
T60	M14	13,25	80	25,5	38	0,346	6271780	ITX 32 T60
T70	M16	15,55	80	25,5	38	0,383	6272080	ITX 32 T70
T80	M18	17,58	80	25,5	38	0,416	6273640	ITX 32 T80
T90	M20	19,95	80	25,5	38	0,455	6276230	ITX 32 T90
T100	M22	21,16	80	25,5	38	0,461	6276310	ITX 32 T100